

# DIGITAL INDICATORS

Dorsey offers the most popular styles of digital indicators to complement our gages. Use the matrix below to select the proper indicator for your application. Please note that we offer many other digital indicators. Contact us if your requirements are not met by these selections.

	PART#	RANGE	RESOLUTION	ACCURACY	FEATURES/DESCRIPTION
 STYLE 1	MT543-683B	.50" / 12mm	.0005" / 0.01mm	< .0008"	ID-S series, SPC output, inch/metric select, rotating face, capacitive system, 20,000 hour battery life # SR44
	MT543-693B	.50" / 12mm	.0001" / .001mm	< .00012"	
	MT543-253B	.50" / 12mm	.0001" / .001mm	< .00012"	ID-C series, same as above but adds preset capability, go/no go tolerancing, 5,000 battery life #SR44
	MT543-453B	1.00" / 25mm	.0001" / 0.001mm	< .00012"	
	MT543-252B	.50" / 12mm	.00005" / 0.001mm	< .00012"	
 STYLE 2	CBG-3600	.60" (ANSI/AGDI#2)	.00005", / .0001", .0005", .001", or select- able	+/- .00005"	Inch/Metric selectable, selectable resolution, SPC output, rotating face, max hold, double lithium battery (approx. 300 hours of on time)
	CBG-3110	1.00" (ANSI/AGD#3)			
	CLG-3600	.60" (ANSI/AGDI#2)			Includes same features as Style 4 above, but also includes absolute and preset modes, min hold mode, hi/low tolerance presets, TIR mode and feature lock
	CLG-3100	1.00" (ANSI.AGD#3)			
 STYLE 3	MEDI-10102	+/- .040"	.00005" / 0.001mm or .0001" / 0.002mm or selectable	+/- .5% OVER +/- .040" +/- .25% OVER +/- .020"	Inch/Metric switchable, 3/8" dia. stem, preset functions, SPC output, double lithium batteries allow approximately 3000 hours of on time use, optional longer travel or 8mm diameter stem
	MEDI-20102	+/- .040"	.00002" / 0.0005mm		
 STYLE 4	M2033102	+/- .100" or +/- .040"	.0001" / 0.001mm or .0005" / 0.005mm	+/- .35%	Inch/Metric switchable, selectable resolution, analog fan, Min/Max/TIR, hold function, tolerance, - + signs, 3/8" stem, 2.75" x 3.5" face size, 1 year battery life
	M2033112	+/- .100" or +/- .040"	.00002"	+/- .35%	Includes same features as above, but also includes RS232 output
 STYLE 5	FV54520790	.50"	.00005" / 0.001mm	+/- .0001"	Sylvac Swiss electronic package, OPTO RS232 output, inch/metric switchable, hold function, preset, single lithium battery #CR2032 4500 hour life, face rotates 270 degrees
	FV54520777	1.00"			
	FV54520875	.50"	.00005" / 0.001mm or .0005" / 0.01mm	+/- .00008"	Includes same features as Style 1 above, also includes Min/Max/TIR modes, tolerance signal lights, selectable resolution
	FV5420888	1.00"			

Note: All indicator part #'s shown above include a standard flat back. Contact us for other optional backs & accessories.

Proudly made in the USA

